

# vStor

Enterprise class media shared storage appliance

**IEEI.TV** [www.ieei.tv](http://www.ieei.tv) Contact: Dennis Bress 714-878-1276 Email: [dennis@ieei.com](mailto:dennis@ieei.com)















 Collaborate

 Store

 Edit

 Share

-  Certified support for Adobe video tools
-  Compatible with any editing software
-  Interoperable with all operating systems and codecs
-  Easy to use, integrated web-based interface for system management
-  Designed for a media-centric production environment
-  Ready to run Apace web apps like PostMAM, Finder, and USM
-  SSD-ready
-  Edit with native files over the network real-time
-  Easy to deploy without the customers having to change their infrastructure
-  Simple and scalable collaborative workflows for media production environment
-  No client software or license needed
-  Easy to use system and storage management

## Models

P/N	Capacity	Description
V55-2U96T-8bay-DB (HDD) V55-2U128T-8bay-DB (HDD)	96 TB / 128 TB	2U rack-mount, 96TB/128TB (84TB/112TB net) Raw HDD Capacity, 8 bay hot swappable HDDs, single array RAID-5, Dual 10GE 10Gbase-T RJ45/backward compatible to GE, Redundant power supply. Stream up to 50 DV25/HDV, 40 DVCPROHD50, 30 DVCPRO-HD, 20 8-bit Prores/DnxHD 145, 14 10-bit DnxHD/ProRes 220.
V55-2U128T16S-12bay-DB (HDD/SDD)	144 TB	2U rack-mount, 128TB Raw HDD + 16TB Raw SSD, 12 bay hot-swappable drives, single array RAID-5, 4 bay x 4TB SSD and 8 bay x 16TB RAID-5, Quad 10GE 10Gbase-T RJ45/ backward compatible to GE, Redundant power supply. Stream up to 90 DV25/HDV, 60 DVCPROHD50, 40 DVCPRO-HD, 30 8-bit Prores/DnxHD 145, 26 10-bit DnxHD/ProRes 220.
V55-3U192T-16bay-DB(HDD) V55-3U256T-16bay-DB(HDD)	192 TB / 256 TB	3U rack-mount, 192TB/256TB Raw HDD Capacity, 16 bay x 12TB/16TB hot swappable HDDs, Dual array RAID-5, Redundant power supply, Quad 10GE 10GBase-T RJ45 ports/ backward compatible to GE. Stream up to 90 DV25/HDV, 60 DVCPROHD50, 40 DVCPRO-HD, 30 8-bit Prores/DnxHD 145, 26 10-bit DnxHD/ProRes 220.
V55-4U288T-24bay-DB(HDD) V55-4U384T-24bay-DB (HDD)	288 TB / 384 TB	4U rack-mount, 288TB/385TB Raw capacity, 24 bay x12TB/16TB hot swappable HDD triple array RAID-5, Quad 10GE 10GBase-T RJ45 ports/ backward compatible to GE, Redundant power supply. Stream up to 99 DV25/HDV, 66 DVCPROHD50, 44 DVCPRO-HD, 33 8-bit Prores/DnxHD 145, 29 10-bit DnxHD/ProRes 220.
AP-Turbo-kit 1		Hardware upgrade kit offering added gain in performance supporting Apace Applications such as MAM search, encode,etc. with CPU.
AP-GPU-Upgrade		Hardware upgrade kit offering added gain in performance supporting Apace Applications to enhance encode with GPU.

## Hardware Specs



### Dimensions (W x D x H)

mm : 430 x 680 x 88  
inches : 16.93 x 26.8 x 3.5

### Hard Drive Slots

8 or 12 x 3.5" hot swap drive trays

### Connectivity

1GE  
10GE (Optional)

### Weight

kgs : 23.5  
lbs : 51.8

### Power Supply

800W 1+1 redundant PSU PMBus 1.2 80+ Platinum

### Mounting

Standard : 28" tool-less slide rail



### Dimensions (W x D x H)

mm : 430 x 680 x 133  
inches : 17 x 26.8 x 5.2

### Hard Drive Slots

16 x 3.5" hot swap drive trays

### Connectivity

1GE  
10GE/40GE (Optional)

### Weight

kgs : 34  
lbs : 75

### Power Supply

800W 1+1 redundant PSU PMBus 1.2 80+ Platinum

### Mounting

Standard : 28" tool-less slide rail



### Dimensions (W x D x H)

mm : 430 x 680 x 177  
inches : 19 x 26.8 x 7

### Hard Drive Slots

24 x 3.5" hot swap drive trays

### Connectivity

1GE  
10GE/40GE (Optional)

### Weight

kgs : 37  
lbs : 81

### Power Supply

1010W 1+1 redundant PSU PMBus 1.2 80+ Platinum

### Mounting

Standard : 28" tool-less slide rail

\*Features subject to change without notice.